


## 30V<sub>DS</sub> N-Channel Enhancement Mode MOSFET

### Features



- $V_{DS}=30V, I_D=3.2A$
- $R_{DS(ON)}=47m\Omega$  (TYP.)  $V_{GS}=10V$
- Reliable and Rugged
- Avalanche Rated
- Low On-Resistance

SOT-23



### Applications

- Load Switch
- Power management in portable/desktop PCs
- DC/DC conversion



### Ordering Information

| Device | Package |         | Marking | Package Qty. |
|--------|---------|---------|---------|--------------|
| CJ2306 | SOT-23  | Pb-Free | S6      | 3000pcs/Reel |

### Absolute Maximum Ratings ( $T_C=25^{\circ}C$ , unless otherwise noted)

| Parameter                                       | Symbol         | Value    | Unit        |
|-------------------------------------------------|----------------|----------|-------------|
| Drain-Source Voltage ( $V_{GS}=0V$ )            | $V_{DS}$       | 30       | V           |
| Gate-Source Voltage ( $V_{GS}=0V$ , static)     | $V_{GS}$       | $\pm 20$ | V           |
| Continuous Drain Current ( $T_C=25^{\circ}C$ )  | $I_D$          | 3.2      | A           |
| Continuous Drain Current ( $T_C=100^{\circ}C$ ) |                | 0.62     | A           |
| Maximum Power Dissipation ( $T_C=25^{\circ}C$ ) | $P_D$          | 0.75     | W           |
| Operating, Storage Temperature Range            | $T_J, T_{STG}$ | -55~150  | $^{\circ}C$ |

## Thermal Characteristics

| Parameter                              | Symbol          | Min. | Typ. | Max. | Unit                        |
|----------------------------------------|-----------------|------|------|------|-----------------------------|
| Thermal Resistance,Junction-to-Case    | $R_{\theta JC}$ | -    | 60   | -    | $^{\circ}\text{C}/\text{W}$ |
| Thermal Resistance,Junction-to-Ambient | $R_{\theta JA}$ | -    | 125  | -    | $^{\circ}\text{C}/\text{W}$ |

## Electrical Characteristics

| Parameter                        | Symbol       | Test Conditions               | Min. | Typ. | Max.      | Unit       |
|----------------------------------|--------------|-------------------------------|------|------|-----------|------------|
| Drain-Source Breakdown Voltage   | $BV_{DSS}$   | $V_{GS}=0V, I_D=250\mu A$     | 30   | -    | -         | V          |
| Zero Gate Voltage Drain Current  | $I_{DSS}$    | $V_{DS}=24V, V_{GS}=0V$       | -    | -    | 1         | $\mu A$    |
| Gate -Source Leakage Current     | $I_{GSS}$    | $V_{GS}=\pm 12V, V_{DS}=0V$   | -    | -    | $\pm 100$ | nA         |
| Gate Threshold Voltage           | $V_{GS(th)}$ | $V_{DS}=V_{GS}, I_D=250\mu A$ | 1    | -    | 3         | V          |
| Drain-Source On-stage Resistance | $R_{DS(ON)}$ | $V_{GS}=10V, I_D=2.8A$        | -    | 38   | 48        | m $\Omega$ |
|                                  |              | $V_{GS}=4.5V, I_D=2.5A$       | -    | 52   | 66        |            |

## Dynamic Characteristics

| Parameter                    | Symbol       | Test Conditions                                                  | Min. | Typ. | Max. | Unit |
|------------------------------|--------------|------------------------------------------------------------------|------|------|------|------|
| Input capacitance            | $C_{iss}$    | $V_{DS}=15V$<br>$V_{GS}=0V$<br>$f=1MHz$                          | -    | 305  | -    | pF   |
| Output capacitance           | $C_{oss}$    |                                                                  | -    | 65   | -    |      |
| Reverse transfer capacitance | $C_{rss}$    |                                                                  | -    | 29   | -    |      |
| Total Gate Charge            | $Q_g$        | $V_{DS}=15V$<br>$V_{GS}=4.5V$<br>$I_D=5.8A$                      | -    | 3    | -    | nC   |
| Gate Source Charge           | $Q_{gs}$     |                                                                  | -    | 6    | -    |      |
| Gate Drain Charge            | $Q_{gd}$     |                                                                  | -    | 1.6  | -    |      |
| Turn-on delay Time           | $t_{d(on)}$  | $V_{GS}=10V$<br>$V_{DS}=15V$<br>$R_L=2.7\Omega$<br>$R_G=3\Omega$ | -    | 7    | -    | ns   |
| Rise time                    | $t_r$        |                                                                  | -    | 12   | -    |      |
| Turn-off delay Time          | $t_{d(off)}$ |                                                                  | -    | 14   | -    |      |
| Fall time                    | $t_f$        |                                                                  | -    | 6    | -    |      |

## Reverse Diode Characteristics

| Parameter                  | Symbol   | Test Conditions                                | Min. | Typ. | Max. | Unit |
|----------------------------|----------|------------------------------------------------|------|------|------|------|
| Body Diode Forward Voltage | $V_{SD}$ | $V_{GS}=0V, I_{SD}=1A$                         | -    | 0.8  | 1.2  | V    |
| Reverse Recovery Time      | $t_{rr}$ | $V_{GS}=0V, I_{SD}=5A$<br>$d_i/d_t=100A/\mu s$ | -    | 16   | -    | ns   |
| Reverse Recovery Charge    | $Q_{rr}$ |                                                | -    | 9    | -    | nC   |

< Copyright >

All the Patent, Copyright and IP contained in this document belong to HAMOS, shall not be reproduced , copied, or used in other ways without permission.