

-40V_{DS}/±20V_{GS} P-Channel Advanced Mode MOSFET

Features

- V_{DS}=-40V, I_D=-8A
- R_{DS(ON)}=26mΩ (TYP.) V_{GS}=-10V
- Reliable and Rugged
- Avalanche Rated
- Low On-Resistance
- High Current Capability

Applications

- Load Switch
- Power management in portable/desktop PCs
- DC/DC conversion

Ordering Information


Device	package	Device Marking	Package Qty.
CSP40P150	SOP-8	CSP40P150	3000/PCS

Absolute Maximum Ratings (T_a=25°C, unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage (V _{GS} =0V)	V _{DS}	-40	V
Gate-Source Voltage (V _{GS} =0V, static)	V _{GS}	±20	V
Continuous Drain Current (T _a =25°C)	I _D	-8	A
Continuous Drain Current (T _a =70°C)		-5	A
Pulsed Drain Current	I _{DM}	-28	A
Avalanche Energy, Single Pulsed	E _{AS}	115	mJ
Maximum Power Dissipation (T _a =25°C)	P _D	2.5	W
Operating, Storage Temperature Range	T _J , T _{STG}	-55~150	°C

Electrical Characteristics

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =-250μA	-40	-	-	V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =-30V, V _{GS} =0V	-	-	-1	μA
Gate -Source Leakage Current	I _{GSS}	V _{GS} =±20V, V _{DS} =0V	-	-	±100	nA
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D =-250μA	-	-	-2.3	V
Drain-Source On-stage Resistance	R _{DS(ON)}	V _{GS} =-10V, I _D =-1A	-	-	26	mΩ
		V _{GS} =-4.5V, I _D =-1A	-	-	35	



Thermal Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit
Thermal Resistance,Junction-to-Case	$R_{\theta JC}$	-	1	-	$^{\circ}C/W$
Thermal Resistance,Junction-to-Ambient	$R_{\theta JA}$	-	-	-	$^{\circ}C/W$

Dynamic Characteristics

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Input capacitance	C_{iss}	$V_{DS}=-15V$	-	1135	-	pF
Output capacitance	C_{oss}	$V_{GS}=0V$	-	345	-	
Reverse transfer capacitance	C_{rss}	$f=1MHz$	-	20.5	-	
Gate Resistance	R_g	$f=1MHz$	-	-	-	Ω
Total Gate Charge	Q_g	$V_{DS}=-15V$	-	45.7	-	nC
Gate Source Charge	Q_{gs}	$V_{GS}=-10V$	-	8.7	-	
Gate Drain Charge	Q_{gd}	$I_D=-15A$	-	6.3	-	
Turn-on delay Time	$t_{d(on)}$	$V_{GS}=-10V$	-	10.5	-	ns
Rise time	t_r	$V_{DS}=-15V$	-	4	-	
Turn-off delay Time	$t_{d(off)}$	$R_L=1\Omega$	-	35	-	
Fall time	t_f	$R_G=3\Omega$	-	5	-	

Reverse Diode Characteristics

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Body Diode Forward Voltage	V_{SD}	$V_{GS}=0V, I_{SD}=-1A$	-	-	-1.2	V
Reverse Recovery Time	t_{rr}	$V_{GS}=0V, I_{SD}=-15A$	-	18	-	ns
Reverse Recovery Charge	Q_{rr}	$dI/dt=100A/\mu s$	-	15	-	nC

Electrical Characteristics Diagrames




Figure 3. On-Resistance vs. Drain Current and Gate Voltage




Figure 4. On-Resistance vs. Junction Temperature




Figure 5. On-Resistance vs. Gate-Source Voltage




Figure 6. Body-Diode Characteristics




Figure 7. Gate-Charge Characteristics




Figure 8. Capacitance Characteristics




Figure 9. Maximum Forward Biased Safe Operating Area




Figure 10. Single Pulse Power Rating Junction-to-Ambient





Figure 11. Normalized Maximum Transient Thermal Impedance



< Copyright >

All the Patent, Copyright and IP contained in this document belong to HAMOS, shall not be reproduced, copied, or used in other ways without permission.