

Features

- $V_{DS}=100V, I_D=130A$
- $R_{DS(ON)}=4.5m\Omega$ (TYP.) $V_{GS}=10V$
- Reliable and Rugged
- Avalanche Rated
- Low On-Resistance
- High Current Capability

Applications

- Load Switch
- Power management in portable/desktop PCs
- DC/DC conversion

Ordering Information

Device	package	Device Marking	Package Qty.
HGN050N10AL	PDFN5*6	**	5000/PCS

Absolute Maximum Ratings (T_C=25°C, unless otherwise noted)

Parameter	Symbol	Value	Unit
Drain-Source Voltage (V _{GS} =0V)	V _{DS}	100	V
Gate-Source Voltage (V _{GS} =0V, static)	V _{GS}	±20	V
Continuous Drain Current (T _C =25°C)	I _D	130	A
Continuous Drain Current (T _C =100°C)		85	A
Pulsed Drain Current	I _{DM}	550	A
Single Pulsed Avalanche Energy	E _{AS}	400	mJ
V _{DS} Spike 100ns	V _{SPIKE}	90	V
Maximum Power Dissipation (T _C =25°C)	P _D	140	W
Operating, Storage Temperature Range	T _J , T _{STG}	-55~150	°C



Thermal Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit
Thermal Resistance, Junction-to-Case	R _{θJC}	-	-	-	°C/W

Electrical Characteristics

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0V, I _D =250μA	100	-	-	V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =30V, V _{GS} =0V	-	-	1	μA
Gate -Source Leakage Current	I _{GSS}	V _{GS} =±20V, V _{DS} =0V	-	-	±100	nA
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D =250μA	2	-	4	V
Drain-Source On-stage Resistance	R _{DS(ON)}	V _{GS} =10V, I _D =20A	-	-	4.5	mΩ
Body Diode Forward Voltage	V _{SD}	V _{GS} =0V, I _{SD} =1A	-	-	1.2	V

PDFN5*6



Dynamic Characteristics

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Input capacitance	C_{iss}	$V_{DS}=15V$ $V_{GS}=0V$ $f=1MHz$	-	3230	-	pF
Output capacitance	C_{oss}		-	1000	-	
Reverse transfer capacitance	C_{rss}		-	20	-	
Gate Resistance	R_g	$f=1MHz$	-	-	-	Ω
Total Gate Charge	Q_g	$V_{DS}=15V$ $V_{GS}=10V$ $I_D=20A$	-	54	-	nC
Gate Source Charge	Q_{gs}		-	16.5	-	
Gate Drain Charge	Q_{gd}		-	16.5	-	
Turn-on delay Time	$t_{d(on)}$	$V_{GS}=10V$ $V_{DS}=15V$ $R_L=0.75\Omega$ $R_G=3\Omega$	-	14.3	-	ns
Rise time	t_r		-	20.8	-	
Turn-off delay Time	$t_{d(off)}$		-	57.7	-	
Fall time	t_f		-	31.8	-	
Reverse Recovery Time	t_{rr}	$V_{GS}=0V, I_{SD}=20A$ $dI/dt=500A/\mu s$	-	-	-	ns
Reverse Recovery Charge	Q_{rr}		-	-	-	nC

Electrical Characteristics Diagrames




Figure 5. On-Resistance vs. Gate-Source Voltage




Figure 6. Body-Diode Characteristics




Figure 7. Gate-Charge Characteristics




Figure 8. Capacitance Characteristics




Figure 9. Maximum Forward Biased Safe Operating Area





Figure 10. Single Pulse Power Rating Junction-to-Case



< Copyright >

All the Patent, Copyright and IP contained in this document belong to HAMOS, shall not be reproduced, copied, or used in other ways without permission